

OCULUS | Easyfield®

Perimeter



OCULUS Easyfield®

The right choice for all your needs

The OCULUS Easyfield® is a full-fledged compact perimeter capable of performing standard automated perimetry of the central visual field up to 30° eccentricity. It has been designed for the combined use as visual field screener and perimeter, offering features usually available only in large units. The spherical bowl with 30 cm (11.81") radius is enclosed into an ergonomically movable cone equipped with a distance adapted lens. The Easyfield® conforms to the Goldmann standard and fulfills the ISO-12866 norm for perimeters.

Measurements of the Easyfield® are carried out using an LED grid with 135 fixed test locations, including the common 30-2, 24-2 and 10-2 patterns. The novel SPARK test strategy leads to faster and more stable threshold tests providing improved diagnostic capabilities. Besides the standard field indices the Easyfield® delivers evaluations of the innovative Glaucoma Staging Program (GSP) and the classifications provided by the Glaucoma Staging System (GSS 2).

Advantages

- **Fast:** Shorter examination times even for threshold tests
- **Compact:** No completely dark room required thanks to the closed construction
- **Lightweight:** Minimal footprint and maximal transportability
- **Robust:** Easy to service in the absence of moving parts
- **More than screening:** Supra-threshold and threshold tests
- **Comprehensive perimetry:** Advanced test strategies, unique evaluation tools, efficient progression analysis.

Models

Easyfield® S

The standard award-winning design with up-to-date features

Easyfield® C

Designed for increased comfort with an adjustable, stylish chin rest



Building on a proven design

Ergonomic and patient-friendly

Hardware Facelift

- The redesigned double head rest with translucent lateral eye shields allows measurements without an eye-patch, saving precious time in the preparation for the test.
- The completely new, vertically adjustable chin rest (Easyfield® C only) improves the quality of examinations by sensibly increasing the comfort of the patients.
- The stylish design of the chin rest is adapted to the ergonomically movable perimeter cone for complete versatility.
- The high resolution camera for better video control image of the patient's eye improves the reliability of exams.
- A spring-loaded double mount offers increased stability for the correction lens holder.
- Standard USB interface offers connectivity of the OCULUS Easyfield® with any external Windows computer, hence network integration is straightforward.



Translucent lateral eye shields



Chin rest



Attachable correction lens holder



Standard Automated Perimetry

Screening


Screening with the OCULUS Easyfield® is most commonly carried out by performing supra-threshold examinations of the central visual field. During these examinations the presented stimulus is always brighter than the one matching the normal threshold value corresponding to the patient's age in the given location. Screening programs have shorter duration and are easier to complete. As a result, an overview of the visual field is obtained, without numerical dB values, but with the identification of peculiar locations.

The Easyfield® employs threshold oriented supra-threshold strategies with 2 or 3 zones, recognizing defects or absolute and relative defects, respectively. The predefined "Screening 24-2" program uses a 2 zones strategy and takes slightly more than a minute per eye to accomplish. Customized screening programs using different test patterns or strategies can be easily created in the device software, with the possibility to adapt to any special requirement.

Threshold measurements

The most complete information about the visual field can be obtained by determining sensitivity threshold values in all locations of a test pattern using strategies for threshold measurements. The OCULUS Easyfield® perimeter offers various ways for threshold measurements:

- **Full Threshold:** The classical 4-2 dB staircase strategy using two reversals in the patient's answer to deliver a threshold value.
- **Fast Threshold:** Bracketing strategy using variable steps and taking advantage of already measured locations.
- **CLIP¹⁾:** Strategy using stimuli with continuously increasing luminance. Threshold value is assigned the moment the stimulus is perceived.
- **SPARK²⁾:** Fast and averaged threshold strategy based on statistical correlations between threshold values measured in different locations.




Printout of a screening examination

¹⁾ CLIP – Continuous Light Increment Perimetry

²⁾ SPARK is not an acronym, the name of the strategy was inspired by the appearance of the stimuli during perimetry

Result Printout

All information at a glance



Printout of a threshold examination

Fighting Glaucoma

Measurement – Assessment – Progression

Increased Precision: The new SPARK threshold strategy

The SPARK¹⁾ strategy is based on statistical relationships between threshold values corresponding to different locations in the glaucomatous visual field, derived after analyzing more than 90,000 perimetric examinations. The large amounts of available statistical data make fast and very precise measurements of the threshold values in the central visual field possible. The ingenious modular structure of the method in four phases allows a diversified use of the SPARK strategy in the clinical practice:

- **SPARK Precision** is the full-fledged version of SPARK. The complete visual field examination of glaucoma patients is performed in 3 minutes per eye; the averaged results of the four phases present an


outstanding stability and repeatability, making possible an improved progression analysis. The strategy is available as an additional option for Easyfield®.

- **SPARK Quick** is the strategy for follow-up or screening examinations. Only 1:30 minutes per eye are necessary.
- **SPARK Training** is ideal for patient training. This 40 seconds measurement can also be used for screening.

The SPARK strategy is fine-tuned for use in clinical examinations of glaucoma patients. In order to be used in suspected neurological pathologies, alternative versions of the above methods, labeled SPARK-N, are available for the OCULUS Easyfield®.

Advanced assessment: Glaucoma Staging System (GSS 2)


The Glaucoma Staging System²⁾ classifies the visual field results using the values of the mean defect (MD) and the pattern standard deviation (PSD or CPSD). The representative point of the examination is placed on a diagram according to the values of the perimetric indices. The diagram displays clearly separated regions for different diagnostic stages related to the advance of the disease (Stage 0 – Stage 5); at the same time, generalized, localized and mixed defects are distinctly identified.



Display of the GSS 2 assessment

¹⁾ M. González de la Rosa, J Glaucoma 2012

²⁾ P. Brusini, S. Filacorda, J. Glaucoma (2006) 15: 40–46



GSP results display

Beyond field indices: Glaucoma Staging Program (GSP)


This novel evaluation module performs a thorough assessment of individual visual field findings using modern algorithms of pattern recognition. Besides the unique contribution to early glaucoma diagnosis, GSP¹⁾ can substantiate the clinical evaluation of test results. The GSP classification is optimized to reproduce glaucoma expert opinions. The database of GSP includes correlations with the whole clinical picture (including structural changes); this information enables GSP to evaluate the risks for the presence of different glaucoma stages starting from the visual field findings.

Intuitive Green-Yellow-Red color coding helps in fast and reliable interpretation of the findings. The striking novelty of GSP consists in its capability to identify both glaucoma suspect patients and patients with possible pre-perimetric glaucoma using only the measured threshold values.

Efficient progression analysis: Threshold Noiseless Trend (TNT)

The TNT²⁾ software module objectively evaluates changes over time in visual field results. Combined with the fast SPARK strategy, it increases considerably the sensitivity for detecting progression in early glaucoma.

- TNT displays a concise report of the progression analysis with a summary of the most relevant parameters (MD slope, p-values, etc.).
- TNT can distinguish between cases of diffuse or focal progression according to the value of the "Focality Index" (FI).
- TNT uses multiple statistical criteria in establishing progression.
- TNT presents a prediction about the expected visual field for a chosen patient's age.



TNT main display

¹⁾ D. Wroblewski et al, Graefes Arch Clin Exp Ophthalmol 2009

²⁾ M. González de la Rosa and M. González-Hernandez, Br. J. Ophthalmol. 2011; V.T Diaz-Aleman et al., Br. J. Ophthalmol. 2009


Technical Data

OCULUS Easyfield®


Static Perimetry	
Programs	Pre-defined glaucoma, macula, screening and neurological tests User-defined tests
Test patterns	30-2, 24-2, 30x24, 10-2, customized patterns
Strategies	Threshold strategies: SPARK Quick, CLIP, OCULUS Fast Threshold, Full Threshold (4/2) Optional: SPARK Precision Age adapted suprathreshold screening (2-zone, 3-zone, quantify defects)
Examination speed	Adaptive, fast, normal, slow, user-defined
Fixation control	Through central threshold, Heijl-Krakau (using the blind spot), live video image
Result display	Greyscale, dB values (absolute/relative), symbols, probabilities, 3D plot
Reports	Enhanced Glaucoma Staging System (GSS2), Glaucoma Staging Program (GSP), Threshold Noiseless Trend (TNT) progression report
Specifications	
Perimeter bowl radius	300 mm
Max. eccentricity	30°
Stimulus size	Goldmann III
Stimulus colour	White
Stimulus duration	200 ms / user-defined
Stimulus luminance range / increments	0.03 – 3 180 cd/m ² (0.1 – 10 000 asb) / 1 dB
Background luminance	10 cd/m ² (31.4 asb)
Patient positioning	Measurement head with adjustable angle of inclination, adaptable chin rest (Easyfield® C only), double head rest
Software	Device control, patient management, backup, and print software (Windows®) Built-in networking, easy EMR-integration, DICOM compatibility
Interface	USB
Technical specifications	
Dimensions (W x D x H)	Easyfield® S: 274 x 370 – 470 x 314 – 429 mm (10.8 x 14.6 – 18.5 x 12.4 – 16.9 in) Easyfield® C: 316 x 506 – 540 x 320 – 435 mm (12.4 x 19.9 – 21.3 x 12.6 – 17.1 in)
Weight	Easyfield® S: 4.6 kg (10.1 lbs) Easyfield® C: 7.4 kg (16.3 lbs)
Max. power consumption	26 W
Voltage, Frequency	100 – 240 V AC, 50/60 Hz
Recommended computer specifications	Intel® Core™ i5, 4 GB memory, 500 GB HDD, Intel® HD Graphics 520, Windows 7 Pro

CE in accordance with Medical Device Directive 93/42/EEC

Easyfield® S



Easyfield® C



WWW.OCULUS.DE

OCULUS Optikgeräte GmbH

Postfach • 35549 Wetzlar • GERMANY
Tel. +49 641 2005-0 • Fax +49 641 2005-295
Email: export@oculus.de • www.oculus.de

- OCULUS Asia, info@oculus.hk
- OCULUS Brasil, info@oculusbrasil.com.br
- OCULUS Canada, sales@oculus.ca
- OCULUS Czechia, oculus@oculus.cz
- OCULUS Iberia, info@oculus.es
- OCULUS Turkey, info@oculus-turkey.com.tr
- OCULUS USA, sales@oculususa.com



OCULUS is certified by TÜV according to
DIN EN ISO 13485 MDSAP